




## ShenZhen Feigete Technology Co.,Limited

ADD: 2 Floor,Building No.51,Bantian No.3 Industrial Area,Longgang District,Shenzhen  
TEL:86-755-82338710 FAX:86-755-28751866 website: www.smartfeigete.com

### Specification Sheet

<b>Model No.:</b> <b>SF106</b>	4G Rugged IP68 Android Tablet	
CPU	MTK6771T, Octa-core 2.1GHZ or MT6877,Octa-core,2.4GHz	
OS	Android 10.0	
RAM/ ROM	Standard 4G+64GB; 6+128GB or 8+256GB for option	
Dimension	291.4*178.8*17mm	
IP Degree	IP68,MIL-STD-810G Standard; 1.5m to 2m drop felling test	
Touch Panel	Gorrilla Class III 10.1" FHD 1200*1920;400nit screen luminance and maximum to 600nits; Readable under strong sunlight and wet fingers	
Camera	Front:5.0M,Rear 13M	
Battery	DC 3.7V/10000mAh	
Network	GSM: 2/3/5/8 WCDMA: 1/2/4/5/8 TDS: 34/39 TDD: 34/38/39/40/41 FDD: 1/2/3/4/5/7/8/12/17/20/ 5G for option CDMA: BC0/BC1	
NFC	Support NFC 13.56MHz Type A/B; ISO 15693 protocols	
UHF	UHF and UHF R2000 for option	
Fingerprint scanner(For option)	FBI certified Biometric Fingerprint Sensor/Reader, Capacitive Touch Screen or Optical Fingerprint sensor ,FIPS 201 image Quality Specification PIV-071006 ,Advanced CMOS Sensor,Resolution:500 DPI,320*480 pixels,8-bit grey level , LDF-Live Finger Detection feature	
IRIS Recognition	Dual camera IRIS recognition for option	
Application range	Military government fingerprint collection, personal fingerprint real name registration, fingerprint payment, fingerprint encryption	
Wifi	802.11b/g/n support 2.4/5.0 GHz,dual band	
Bluetooth	Bluetooth5.0	
GPS	GPS, BDS,GLONASS and Reserve U-Blox M8N pads optional	
Laser Barcode scanner	2D barcode scanner supported for option	
G-sensor	G sensor 3 axis	
MIC	Built-in microphone	
Speaker	8Ω / 2.5W fidelity speakers * 2	
Light sensor	Support	
Distance sensor	Support	
SIM Card	Support	
Ports	3.5mm stereo phone jack; HDMI,RJ45,RS232, RS485, DB9, Capacitive pen; magentic pen; CAN for option	
USB port	1* Type C; 1* Type A support OTG;	
TF	1x miniSD scard up to 128G	
Earphones SIM Card	3.5mm stereo phone jack	
Operation temperature	-20°C~60°C	
Humidity	95%	
Storage temperature	-40°C~70°C	
DC Charging	5V/3A support fast charging	
Certificate	CE/ROSH /3C/FCC	